

IN THE SPECIFICATION

Please make the following changes to the specification and the abstract:

- On page 3, line 7, after "secured to" insert --a--;
- On page 3, line 20, after "orientation" change "for" to --or--;
- On page 3, line 21, change "or in" to --and--;
- On page 3, line 22, after "show" change "treadmills" to --treadmill--;
- On page 4, line 19, after "gas" change "gylander" to --cylinder--;
- On page 5, line 9, after "portion of" change "a" to --an--;
- On page 6, line 29, after "running" insert a --,(comma)--;
- On page 7, line 3, after "12" insert a --,(comma)--;
- On page 7, line 10, after "also" change "been" to --be--;
- On page 7, line 15, after "of" insert --the drive--;
- On page 7, line 16, delete the comma after "FIG. 1";
- On page 7, line 23, delete the comma after "(FIG. 4)";
- On page 8, line 10, after "in" insert --the--;
- On page 8, line 30, change "foot means" to --feet means--;
- On page 9, line 2, change "62" to --59--;
- On page 9, line 3, change "63" to --63D--;
- On page 9, line 7, change "67" to --67W--;
- On page 9, line 8, after "tread" change "deck" to --base--;
- On page 9, line 12, change "65" (both occurrences) to --65L--;
- On page 9, line 12, change "67" (both occurrences) to --67W--;
- On page 9, line 16, change "62" to --59--;
- On page 9, line 25, change "67" to --67W--;
- On page 10, line 9, after "downward" delete "74";
- On page 10, line 9, change "76" to --77--;
- On page 10, line 10, change "(incross section)" to --(in cross section),--;
- On page 10, line 26, after "80" insert --, 90--;

On page 11, line 20, after "114" insert --and--;

On page 12, line 17, after "tread" change "deck" to --base--;

On page 12, line 29, insert a comma after "hazardous";

NE On page 13, line 11, after "left" change "leg" to --foot--;

On page 13, line 11, after "right" change "leg" to --foot-- (both occurrences);

On page 13, line 12, after "left" change "leg" to --foot--;

On page 13, line 16, change "legs 134" to --feet 34--;

On page 14, line 23, change "264" to --265--;

On page 14, line 27, change "264" to --265--;

On page 14, line 29, change "264" to --265--;

On page 14, line 30, change "motor 264" to --motor 265--;

On page 15, line 11, after "seen" insert --in--;

On page 15, line 11, after "right" change "leg" to --foot--;

On page 15, line 12, after "left" change "leg 166" to --foot 160--;

On page 15, line 18, after "cantilever" insert --320--;

On page 15, line 19, change "324" to --325--;

On page 15, line 28, change "cylinder" to --spring--;

On page 16, line 3, change "shaft" to --cross member--;

On page 16, line 10, at the beginning of the line, change "shaft" to --extension--;

On page 16, line 12, change "cylinder" to --spring--;

On page 16, line 13, change "cylinder" to --spring--;

On page 16, line 16, at the beginning of the line, change "A" to --In--;

On page 16, line 20, after "extension" change "324" to --322--;

On page 16, line 29, after "of the" change "support" to --upright--;

On page 17, line 9, after "apertures" (2nd occurrence) insert --363--;

On page 17, line 10, after "clamp" insert --368--;

NE On page 17, line 10, change "clamping structure" to --top clamp--;

On page 17, line 16, change "cross member 104" to --support bar 104-- (both occurrences);

On page 17, line 18, change "cross member 104" to --support bar 104--;

On page 17, line 25, delete "392";

On page 17, line 26, delete "392";

On page 18, line 1, delete "392";

On page 18, line 4, delete "392";

On page 18, line 9, delete "392";

On page 18, line 19, at the beginning of the line, change "spring" to --sponge--;

On page 18, line 20, change "affected" to --effected--;

On page 18, line 23, insert a comma after "and" and change "particular" to --particularly--;

On page 18, line 26, delete "392";

On page 18, line 28, change "latch member" to --bar--;

On page 18, line 30, after "position" insert --shown--;

On page 19, line 1, change "latch member" to --bar--;

On page 19, line 4, delete "392";

On page 19, line 5, delete "392";

On page 19, line 6, change "spring means" to --sponge--; thereafter delete "or" and delete the comma after "406";

On page 19, line 9, delete "392" and in its place insert a --,(comma)--;

On page 19, line 24, after "gravity" change "446" to --440--;

On page 19, line 26, change "center of gravity of the overall treadmill 458" to read --center of gravity 458 of the overall treadmill--;

On page 20, line 4, after "base" change "436" to --434--;

On page 20, line 11, delete "446";

On page 21, line 6, after "shown" insert --in--;

NE On page 21, line 1, insert a comma after "course";

- On page 21, line 19, insert a comma after "course";
- On page 22, line 3, insert a comma after "114" and change "FIG. 4" to --FIG. 1--;
- On page 22, line 11, change "478" to --477--;
- On page 22, line 14, after "handle" change "485" to --484--;
- On page 22, line 19, change "480" to --481--;
- On page 22, line 26, after "tread" change "deck" to --base--;
- On page 23, line 4, change "roller" to --front pulley--;
- On page 23, line 5, after "rear" change "roller" to --pulley--;
- On page 23, line 11, after "4," insert --it--;
- On page 23, line 13, change "FIG." to --FIGS.--;
- On page 23, line 26, change "FIGS. 13 and 14," to --FIGS. 12 and 13,--;
- On page 24, line 7, after "an" change "axel" to --axle--;
- On page 24, line 24, after "member" delete "506";
- On page 24, line 29, change "axel" to --axle--;
- On page 25, line 2, after "torque" insert a --,(comma)--;
- On page 26, line 11, after "support" change "512" to --515--;
- On page 26, line 24, after "536" insert a --,(comma)--;
- On page 27, line 7, after "F" change "with" to --from--;
- On page 27, line 17, after "member" change "510" to --519--;
- On page 27, line 24, after "support" change "512" to --515--;
- On page 27, line 30, change "552" to --556--;
- On page 28, line 23, after "support" change "512" to --515,--;
- On page 28, line 29, delete "572";
- On page 29, line 10, delete the comma after "features"; and
- On page 32, line 7, after "and" insert --in--.